

MODEL	SQ	TORQUE*	BOLT SIZES	H	L	R	W	RPM	WEIGHT W/O ARM	WEIGHT W/ARM
LPW - .25	3/4"	85-250 ft. lbs (115-338 Nm)	1/2" to 7/8"	7.06/179.32	7.15/181.61	1.25/38.1	2.72/69.1	65	7.2/3.3	8.4/3.8
LPW - .5	3/4"	175-500 ft. lbs (237-678 Nm)	1/2" to 1"	7.32/185.93	8.07/204.89	1.25/38.1	2.74/69.5	24	7.2/3.3	8.4/3.8
LPW - 1	3/4"	200-1,250 ft. lbs (271-1695 Nm)	7/8" to 1 3/8"	7.06/179.32	8.82/224.03	1.25/38.1	2.72/69.1	6.5	8.8/4.0	10.0/4.5
LPW - 3	1"	856-3,180 ft. lbs (1161-4312 Nm)	1 1/4" to 1 7/8"	7.94/201.70	11.11/282.19	1.31/33.27	3.53/89.6	5	15.75/7.1	19/8.6
LPW - 5	1 1/2"	1,200-5,200 ft. lbs (1627-7050 Nm)	1 1/2" to 2"	7.93/201.42	12.24/310.90	1.81/46.0	3.70/93.9	2.5	20.05/9.1	26.85/12.2
LPW - 8	1 1/2"	1,775-8,035 ft. lbs (2407-10089 Nm)	1 1/2" to 2 1/2"	8.03/210.82	13.00/330.20	1.81/46.0	3.69/93.7	1.5	26.5/12.0	34.5/15.6

All tools and pumps are subject to a 13 months free repair/replacement guaranty on failure. Data subject to change without notice. *Max. Torque Range.



FRL UNIT

Filter, Regulator and Lubrication Unit. for use with all torque guns.
Optional Silencer Unit to reduce operational noise by 35%, down to a very low 70-75 Db. 1FRL Saa.10.T.O.,1