

Multipurpose Cylinders

Series : LMC

Capacity : 5 to 30 Ton | Working Pressure : 700 Bar



- High strength alloy steel construction.
- Hard chrome plating for cylinder bore and piston rod to resist corrosion.
- Quick spring retraction.
- Collar threads for easy mounting.
- Can be operated in horizontal and vertical positions.



All models are supplied with dust seal to increase the cylinder life.

Model	Cylinder Capacity (Tons)	Stroke (mm)	Cylinder Effective Area (cm ²)	Oil Capacity (cc)	Retracted Height (mm)	Extended Height (mm)	Cylinder Out Dia. (mm)	Piston Rod Dia. (mm)	Collar Thread (mm)	Collar Thread Length (mm)	Metric Tonnes @ 700 Bar	Weight (Kg)
					A	B						
LMC 52	5	25	6.38	10	110	135	38	25	35 x 2P	38	4.50	1.0
LMC 55		50		35	134	184						
LMC 57		75		50	165	240						
LMC 510		100		70	184	284						
LMC 515		150		106	234	384						
LMC 105	10	50	15.2	76	133	183	58	38	55 x 2P	30	10.84	2.1
LMC 1010		100		152	183	283						
LMC 1015		150		228	233	383						
LMC 1020		200		304	283	484						
LMC 252	25	25	33.18	86	165	190	88	57	85 x 2P	50	23.67	6.4
LMC 255		50		166	165	215						
LMC 2510		100		332	215	315						
LMC 2515		150		498	265	415						
LMC 2520		200		664	315	515						
LMC 2525		250		867	374	624						
LMC 2530		300		1033	425	725						
LMC 2535		350		1202	476	826						