Series: LBJ




Capacity: 10 - 200 Ton | Stroke Length: 10 mm | Working Pressure: 700 Bar






- Flexi hose connection to fix couplers due to very low height design
- Maximum strock limit marked on the piston



- Single acting load return type cylinders.
- High strength alloy steel construction.
- Hard chrome plating for cylinder bore and piston rod to resist corrosion and provide longer life.
- · Carry handle for heavy cylinders.
- Fitted with standard 3/8" NPT threaded female coupler.



| Model | Cylinder Capacity (Tons) | Stroke (mm) | Effective Area (cm²) | Oil Capacity (cc) | Retracted Height (mm) | Extended Height (mm) | Cylinder Outer Dia (mm) | Piston Rod Dia (mm) | Metric Tonnes . @ | Weight (kg) |
|----------|--------------------------------|----------------|----------------------------|-------------------------|-----------------------------|----------------------------|-------------------------------|---------------------------|-------------------------|----------------|
| | | | | | A | В | С | D | 700 Bar | |
| LBJ1010 | 10 | 10 | 15.9 | 16 | 30 | 40 | 85 | 45 | 11.42 | 1.5 |
| LBJ2010 | 20 | | 31.2 | 31 | 35 | 45 | 100 | 63 | 22.12 | 2 |
| LBJ3010 | 30 | | 44.2 | 45 | 40 | 50 | 120 | 75 | 32.11 | 3.5 |
| LBJ5010 | 50 | | 78.5 | 79 | 50 | 60 | 155 | 100 | 56.37 | 7.5 |
| LBJ10010 | 100 | | 153.9 | 154 | 70 | 80 | 210 | 140 | 109.89 | 19 |
| LBJ15010 | 150 | | 227 | 227 | 75 | 85 | 260 | 170 | 161.98 | 31 |
| LBJ20010 | 200 | | 314.2 | 314 | 80 | 90 | 300 | 200 | 224.06 | 45 |

8 www.liftoncanada.com