Torque Wrench & Tensioner Accessories





Hydraulic Hose for Torque Wrench set.

Model	Length (Metres)	Description
LTH4-M	4	Hydraulic twin hose with
LTH6-M	6	quick release couplers on both ends. (Fitted with MCF- 142 & FCM-142 couplers) Working pressure 700 Bar.
LTH10-M	10	
LTH12-M	12	

^{*} Hoses with different length are available upon request



Hydraulic Quick Connect Coupler.

Model	Thread Size	Description
FWC-142	1/4" NPTF	Female coupler. Working pressure 700 Bar.
MWC-142	1/4" NPTF	Male coupler. Working pressure 700 Bar.



Hydraulic Quick Connect Threaded Coupler.

Model	Thread Size	Description
FCM-142	1/4" NPTM	Female coupler. Working pressure 700 Bar.
MCF-142	1/4" NPTF	Male coupler.
MCM-142	1/4" NPTM	Working pressure 700 Bar.



Hydraulic Nipple.

Model	Thread Size	Description
LF-14	1/4" NPTM x 1/4" NPTM	Male adaptor. Working pressure 700 Bar.



Hydraulic High Pressure Quick Connect Coupler.

Model	Thread Size	Description
FTC-144	1/4" BSPF	Female coupler. Working pressure 1500 Bar.
MTC-144	1/4" BSPF	Male coupler. Working pressure 1500 Bar.



Hydraulic High Pressure Nipple.

Model	Thread Size	Description
LF-15	1/4" BSPM x 1/4" BSPM	Male adaptor. Working pressure 1500 Bar.
LF-1914UHP	9/16" UNF x 1/4" BSP	Male adaptor. Working pressure 1500 Bar.

48 www.liftoncanada.com