

Reducer Inserts for Low clearance Hydraulic Wrench



- High strength alloy steel.
- Supplied with holding ring.
- Customized sizes available up on request.



Metric Sizes	Out side Hexagon	In side Hexagon	For Model ITZ-2	For Model ITZ-4	For Model ITZ-8	For Model ITZ-14	For Model ITZ-20	
	A/F Size(mm)	A/F Size(mm)						
	32	27	2R 32-27	4R 32-27				
	36	27	2R 36-27	4R 36-27				
		30	2R 36-30	4R 36-30				
	41	27	2R 41-27	4R 41-27				
		30	2R 41-30	4R 41-30				
		32	2R 41-32	4R 41-32				
	46	30	2R 46-30	4R 46-30				
		32	2R 46-32	4R 46-32				
36		2R 46-36	4R 46-36					
50	32	2R 50-32	4R 50-32					
	36	2R 50-36	4R 50-36					
	41	2R 50-41	4R 50-41					
55	36		4R 55-36					
	41		4R 55-41					
	46		4R 55-46	8R 55-46				
60	41		4R 60-41	8R 60-41				
	46		4R 60-46	8R 60-46				
	50		4R 60-50	8R 60-50				
65	46		4R 65-46	8R 65-46				
	50		4R 65-50	8R 65-50				
	55		4R 65-55	8R 65-55				
70	46			8R 70-46				
	50			8R 70-50				
	60			8R 70-60				
75	50			8R 75-50				
	55			8R 75-55				
	65			8R 75-65	14R 75-65			
80	55			8R 80-55	14R 80-55			
	60			8R 80-60	14R 80-60			
	70			8R 80-70	14R 80-70			
85	60			8R 85-60	14R 85-60			
	65			8R 85-65	14R 85-65			
	75			8R 85-75	14R 85-75			
90	65			8R 90-65	14R 90-65			
	70			8R 90-70	14R 90-70			
	80			8R 90-80	14R 90-80			
95	70			8R 95-70	14R 95-70			
	75			8R 95-75	14R 95-75			
	85			8R 95-85	14R 95-85	20R 95-85		
100	80				14R 100-80		20R 100-80	
	85				14R 100-85		20R 100-85	
	90				14R 100-90		20R 100-90	
105	85				14R 105-85		20R 105-85	
	90				14R 105-90		20R 105-90	
	95				14R 105-95		20R 105-95	
110	90				14R 110-90		20R 110-90	
	95				14R 110-95		20R 110-95	
	100				14R 110-100		20R 110-100	
115	95				14R 115-95		20R 115-95	
	100				14R 115-100		20R 115-100	
	105				14R 115-105		20R 115-105	
120	100						20R 120-100	
	105						20R 120-105	
	110						20R 120-110	
130	110						20R 130-110	
	115						20R 130-115	
	120						20R 130-120	
145	115							
	120							
	130							