

- Wrench clicks and momentarily release, when set torque is reached, Resulting in fast and efficient operation.
- The 45-tooth reversible ratchet head results in both clockwise and Counter clockwise, fine increment operation.
- Dual scale reading- imperial and metric.
- +/- 4% Accuracy in clockwise, direction exceeds specifications.
- Ergonomic soft TPR | Metal grips are comfortable to use.
- Lock Knob secures selected torque from accidental change.


## Window Scale Reading Type Series : LR



Window Scale

Model	Square Drive	Torque Range		Length (mm)	Weight (Kg)
		N.m	L.b.ft		
LR12060	1/2"	10-60	9-45	360	0.82
LR12125	1/2"	25-125	22-90	420	0.9
LR12200	1/2"	40-200	30-150	460	1.02
LR12335	1/2"	65-335	50-250	520	1.16
LR34400	3/4"	80-400	60-300	700	2.75

## Micro Meter Reading Type Series : LM



Micrometer

Model	Square Drive	Torque Range		Length (mm)	Weight (Kg)
		N.m	L.b.ft		
LM34500	3/4"	100-500	80-400	700	2.83
LM34800	3/4"	160-800	120-600	1040	5.9
LM34100	3/4"	200-1000	150-750	1040	5.9
LM11000	1"	200-1000	150-750	1040	5.9
LM11500	1"	300-1500	200-1100	1250	9.2
LM12000	1"	400-2000	300-1500	1250	9.2
LM13000	1"	600-3000	400-2200	1250	10.50